



Recycling Equipment, Inc.

EPS Densifier

Pre-Breaker/Compactor

REI offers a line of all electro-mechanical EPS Densifiers for volumes from 50 lbs. to 500 lbs. per hour, producing truckloads of 40,000 lbs. for optimum efficiency. Allows maximum reduction of EPS, reducing storage, disposal and transportation costs. They can be fed safely by hand or by conveyor.

EPS Styrofoam Densifier Specifications

| Model | SD100 | SD200 | SD300 |
|--|-----------|---------|---------|
| Overall Width--in | 20 | 26 | 30 |
| Overall Height--in | 69 | 72 | 94 |
| Overall Length--in | 118 | 150 | 216 |
| Charge Opening Width--in | 14 | 20 | 25 |
| Charge Opening Length--in | 32 | 32 | 40 |
| EPS Block Size--in | 5.5 x 5.5 | 12 x 12 | 15 x 15 |
| Production Capacity--lb/Hour | 55 | 220 | 440 |
| Compressed EPS Density--lb/cubic foot | 20-25 | 20-25 | 20-25 |
| EPS Compression Ratio | 50 to 1 | 50 to 1 | 50 to 1 |
| Motor--hp | 5 | 12.5 | 20 |
| Unit Weight--lb | 780 | 2,700 | 4,500 |



These densifiers are ideal for Furniture Distributors, Food Distributors, Consumer Electronic Distributors, Wholesales Centers and Appliance Distributors.



Processed Logs ready for the recycler, approx. 1000 lbs. per pallet load ready to ship. Logs fit perfectly on a 48" x 48" pallet.