GORILLA Two Ram

For ONP, OCC, High Grade Paper, Solid Waste, PET, HDPE, Film, Cans, Electric Scrap, White Goods, Non-Ferrous Metals, RDF

Key Advantages:

- Heavy Duty Construction with Hardox 450 replaceable wear liners
- 232 Tons of Compaction force
- 60% Ram penetration – greatly reduces memory in plastics and other materials – compacts on every stroke
- Category III Safety levels – standard
- Flooded Suction Power Unit
- Soft Start main motor starting—reduces energy consumption
- HMI System – 10” touch screen easy to use with multiple operating areas including on the floor as well as elevated on the bale chamber or eject ram

HARRIS AMERICAN

HarrisAmericanCo.com

GORILLA TWO RAM

Bale Size: 45” x 31” x 63”
Feed Opening: 65” x 94”
Main Cylinder: 13” bore w/ 232 tons of force and 277psi
System Pressure: 3500 psi
Eject Cylinder: 9” at 111 tons of force
Power Saving Soft Start: Standard
Machine Weight: 94,000 pounds

PRODUCTION

	Weights	100S2	100S4	150S4	200T
OCC	1250-1550	10-13	15-18	16-20	23-27
Plastic	1250-1675	4-8	6-12	7-15	10-18
Paper	1375-1750	17-22	22-29	25-33	34-43
UBC	1000-1200	4-9	8-13	8-15	12-17
NF Metals	1500-2400	8-17	12-21	15-27	22-37
MSW	1975-2600	18-28	24-35	27-40	36-54
Hyd. Tank		725	950	950	1600

Production for OCC, Paper, NFM run without Combo Door activated

PRODUCTION OPTIONS

Hopper extension up to 96” (2438mm) high
Elevated operator’s platform
Climate controlled operator’s cab
Feed conveyors
Lower main ram wiper
Remote Operating Controls

HARRIS AMERICAN

BEYOND THE EXPECTED

HarrisAmericanCo.com • 800-710-4994